

Maritime VSAT Terminal v80E

- Cost Effective
- Light Weight
- Easy to Install
- Built-in Wi-Fi



KEY FEATURES

- 3-axis stabilised
- Global Search feature and Gyro enabled NMEA0183
- Compatible with all major modem brands
- Built-in Wi-Fi
- IPX6 standard
- Warranty (2 years for parts and labour)
- 0.6m and 1.0m dish sizes also available

Parameters	Intellian v80E Ku-band Maritime VSAT Antenna
Antenna Size	80cm
Antenna Type	Ring focus
Transmit Peak Gain	39.8dBi @14.25 GHz (excl. radome)
Receive Gain	38.1dBi @11.70 GHz (excl. radome)
Polarisation	Linear
Frequency Range	Tx: 13.75~14.50 GHz Rx: 10.70~12.75 GHz
Min. Operating Elevation	-15°
Antenna Pointing Accuracy	0.2° max in presence of specified ship motions
Tracking Mode	Global Search feature and Gyro enabled NMEA0183
Tracking Speed	10°/sec ²
Cross Pole Isolation	>30dB
Receive G/T	17.8dB/K@12.75 GHz (clear sky, 30° elevation)
BUC Power	6W fixed
Modem Protocol	Comtech, Gilat, Hughes, iDirect, Newtec, Satpath, Spacebridge, UHP
Antenna Interface	Ethernet port (OpenAMIP)/ RS-232/ RS-422 / I/O Console
Azimuth Range	Unlimited
Elevation Angle	-15° to +110°
ACU Size	431mm X 350mm X 44mm
ACU and Antenna Power Consumption (without BUC)	
- Static Power	110W
- Dynamic Power	140W

For more information, please email SAILAS@asiasat.com

AsiaSat Proprietary, 24 August 2022

Distribution of substantively modified versions of this document is prohibited without the explicit permission of AsiaSat